

RCMT

Tolerances:
 INSD = ±0,05
 INSD = ±0,08
 INSD = ±0,10
 S = ±0,05
 S = ±0,13

Size:
 06, 08, 10
 12
 16
 06, 08, 10
 12, 16

AN = 7°

Size	Dimensions in mm		
	INSD	S	D1
0602	6,00	2,38	2,9
0803	8,00	3,18	3,5
10T3	10,00	3,97	4,5
1204	12,00	4,76	4,5
1606	16,00	6,35	5,6

Inserts	Designation	RE	Grades																							
			Coated													Uncoated		Cermet								
			TP0501	TP1501	TP2501	TP3501	TP200	TP40	TH1000	TH1500	TM2000	TM4000	TK0501	TK1501	TS2000	TS2050	TS2500	CP200	CP500	CP600	HX	KX	883	890	TP1020	TP1030
RCMT-F1	RCMT0602M0-F1	-			■	■												■								
	RCMT0803M0-F1	-			■	■		■										■								
	RCMT10T3M0-F1	-			■	■		■										■								
	RCMT1204M0-F1	-		■	■	■		■					■					■								
	RCMT1606M0-F1	-	■	■	■	■																				
RCMT-F2*	RCMT0602M0-F2	-						■							■					■						
	RCMT0803M0-F2	-						■							■		■			■						
	RCMT10T3M0-F2	-						■	■						■					■						
	RCMT1204M0-F2	-						■	■						■					■						
	RCMT1606M0-F2	-							■											■						
RCMT-M3*	RCMT0602M0-M3	-			■	■																				
	RCMT0803M0-M3	-		■	■	■									■											
	RCMT10T3M0-M3	-		■	■	■									■											
	RCMT1204M0-M3	-		■	■	■		■					■	■												
	RCMT1606M0-M3	-	■	■	■	■																				
RCMT-RR94	RCMT1204M0-RR94	-				■																				

■ Stock standard
 Subject to change refer to current price- and stock-list

* Chipbreaker -M3 replacing -F2