


OTHER

• Literature • Cutting Lubricant



The ultimate reference book

- Pocket sized grease / tear proof lay-flat format
- Ideal for engineers, trades people, apprentices, machine shops, tool rooms, technical colleges







L300V2EN

Engineers Black Book - 234 Pages of:

- · Tables
- Standards
- Illustrations
- · Grinding wheels
- Conversion factors
- Tapers
- Lubricantscoolants
- · Bolts and nuts
- Spur gear calculations
- · Tungsten carbide
- Plastics
- Sharpening information

- · G Codes
- · Hardening and tempering
- Formulae
- · Geometrical construction
- · Weights of metal
- Engineering drawing standards
- Tolerances
- · Keys and keyways
- Tapping drill sizes
- · Speeds & feeds
- Equivalent charts and more...

Electrical Black Book - 212 Pages of:

- Electrical safety laws of electricity electrical conductors
- · Electrical codes and standards
- · Electrical conduit and conduit bending
- Electrical formulae and conversion factors transformers and motors
- Electrical socket-outlets, switches and enclosures
- Led lighting, fibre optics and data cabling and more...

Fastener Black Book - 248 Pages of:

- Screw thread fundamentals
- Standards
- · Heat treatment
- · Thread classes
- Grades
- Materials and coatings
- Failures and corrosion
- Thread terminology
- · Tolerances
- Fastener strengths and markings

- Hydrogen
 - embrittlementScrew thread profiles
 - Dimensional specifications DIN / ISO / ANSI
 - Galling
 - · Material selection
 - · Torque control
 - Platings
 - Elevated temperature effects

Discount Group: Z0502

| Description | Edition | Pages | Carton Qty | Bonus | Item# |
|--------------------------------------|---------|-------|------------|--------------------|----------|
| | | | | | L100 |
| Engineers Black Book | 3rd | 234 | 40 | Labelling Tabs | L100V3EN |
| | | | | | L103 |
| Engineers Black Book - Large Edition | 3rd | 234 | 20 | Labelling Tabs | L103V3EN |
| | | | | | L200 |
| Fasteners Black Book | 1st | 248 | 40 | Thread Pitch Gauge | L200V1EN |
| | | | | | L203 |
| Fasteners Black Book - Large Edition | 1st | 248 | 20 | Thread Pitch Gauge | L203V1EN |
| | | | | | L300 |
| Electrical Black Book | 2nd | 212 | 40 | Labelling Tabs | L300V2EN |





Venom Endurance+ Cutting Fluid

Venom Endurance+ Cutting Fluid is a highly efficient cutting and lubricating fluid. Formulated to increase tool life and enhance cutting performance in a broad range of metals including carbon steel, aluminium alloys, copper, brass, bronze and stainless steel.

Mild clinging action helps fluid adhere to the tool and part when vertical work is required.

Venom Extreme Power Cutting Paste

Formulated for superior tool life and cutting performance in carbon steel, aluminium alloys, copper, bronze, stainless steel, nickels, titaniums and other

Venom Extreme Power Cutting Paste is a high performance low melting point lubricant specifically designed to adhere to the cutting edges, even when using additional coolants.

| | | Dis | CO | un | t (| àr(| ou | p Z | 10 | 06 |
|--|--|-----|----|----|-----|-----|----|-----|----|----|
|--|--|-----|----|----|-----|-----|----|-----|----|----|

| Size Ref. | Description | Size | Item# |
|-----------|-----------------------|-------|-----------|
| | | | M800 |
| 0050 | Venom Cutting Fluid** | 50ml | M800 0050 |
| 0250 | Venom Cutting Fluid | 250ml | M800 0250 |
| 0300 | Venom Cutting Spray* | 300g | M800 0300 |
| 0400 | Venom Cutting Paste | 400g | M800 0400 |
| 4000 | Venom Cutting Fluid | 4L | M800 4000 |

*Only available in multiples of 6 **Only available in multiples of 12

EXTREME POWER


CUTTING PASTE

Features

- · Low melting point adheres to cutting edge for greater tool protection
- · Not affected by coolant
- · Lowest torque required for higher performance
- · Reduced friction for extremely high quality surface finish



M800 0400





- · Reduces torque and friction
- · Extends tool life
- · Improves surface finish
- · Accurate thread quality
- · Environmentally friendly mineral oil base with 10% organic coconut oil.

Free from Trichloroethane - low odour.







M800 0250



M800 4000



CUTTING SPRAY

Features

- · Comfort nozzle allows an accurate spray flow in hard-to-reach working areas
- Precise spray flow within 1.5m range
- · Non-flammable
- · Reduces torque and friction
- · Extends tool life
- $\cdot \, \text{Improves surface finish} \\$
- · Accurate thread quality
- Environmentally friendly mineral oil base with 10% organic coconut oil. Free from Trichloroethane - low odour.
- · Suitable for use in non-ventilated areas



M800 0300

